

Rub, De awn,  
& Polish a  
Variety of  
Seeds to  
Increase  
their Test  
Weight &  
Value



- Heavy Wall Drum Design for Superior Longevity
- Hardened Steel Paddles
- Industry Standard 15° Angle on Paddles to Rub & Assist with Product Flow
- TEFC, NEMA Premium Efficient Motors; X Proof Available
- Dust Hood at Discharge of Machine for Containment
- Optional VFD (Variable Frequency Drive) for Easy RPM Adjustment
- 8" + 10" Drums utilize Pneumatic Clean out
- 15" + 20" Drums utilize Heavy Duty Drop out Door for Easy Clean out
- Numerous Models with Various Throughput Capacities Available
- Designed and Made in the USA

Use with Cereals, Turf,  
Forage & Prairie Grass  
Seed, Wild Flower,  
Malted Barley

QSAGE MODEL	CAPACITY APPROX. (BPH, Barley)	HP REQ.	CLEAN OUT	DISCHARGE SPOUT w/ Dust Port
QD-8x18	50-100	3	Pneumatic	Included
QD-10x24	100-200	3 or 5	Pneumatic	Included
QD-10x36	150-300	5 or 7.5	Pneumatic	Included
QD-15x48	200-500	10 or 15	Bottom Gate	Included
QD-15x72	350-600	20 or 25	Bottom Gate	Included
QD-20x48	350-650	15 or 20	Bottom Gate	Included
QD-20x72	400-700	20 or 25	Bottom Gate	Included

### PRODUCT FLOW

